



2X M3 PIN HOLE
FOR MOUNTING




Ø 2.25in
[57.2mm]

2 5/8" - 32
THREAD FOR MOUNT



2X COVER GLASS
CARTRIDGE
LOCK THUMB SCREWS

FOCAL LENGTH
ADJUST
± 4mm



4.01in
[101.8mm]

1mm INITIAL
STAND-OFF

COVER GLASS
CARTRIDGE
Ø 1" x 1/8" 200 PSI MAX

2X X-Y ULTRA
PRECISION
ADJUST

1/8 BSPP
FOR GAS
ASSIST

FOR INFORMATION ONLY
NOT FOR MANUFACTURING

DATE:
7/27/2017

DRAWN BY:
MPM

CHKD BY:
RS

TOLERANCES:
(EXCEPT AS NOTED)

X.XXX = ± 0.005

X.XX = ± 0.01

X.X/X = ± 1/64

ANGULAR: ± 0.5°



37 IRONIA ROAD
FLANDERS NJ 07836
(973) 598-1150
Fax: 598-1151

HAAS DOCUMENT# MMH-25-34-80-SALES

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE.
CONTACT HAAS LTI FOR MORE INFORMATION.

MMH-25-34-80
CUSTOMER DIMENSION DWG

BOM#
NA

SCALE: 1:1/A